



**Bancor BPPR 2
Printer 2**

bancor

BPR2 is the dot matrix printer designed to provide high speed, reliability and high performance for solutions for your front office

BPR2 is a professional multifunctional printer for front office to print on single documents, multiple-and on any passbook.

bancor thanks to more than 30 years of experience in the field of office automation, the great attention to quality conjugated to a high capacity in terms of productivity allowed to obtain a printer at the highest levels of the sector in terms of print quality, print speed and minimal space footprint.

bancor has also designed the device as much ergonomic and stylish, enhancing the small size to achieve an ease use and provide as much space as possible to the desk. The end result makes BPR2 of the smaller specialized printers on the market.

Preliminary Specifications:

Technology

- 24-pin lozenge printing head
- Diameter 0.25 mm and Life 800mln dots

Max Resolution

- 360 x 240 dpi

Font

- OCR A-B, ROMAN, Sans Serif, Italic, Courier
- Others 54 international Character

Printing Speed 10 cpi

VHS	HS	Draft	NLQ	LQ
660	500	370	185	>125
90x180	120x180	180x180	188x182	360x240

Line Length

- 238,76 mm (94 columns a 10 cpi)

Copies

- Single sheet of paper, Multi layer carbon paper up to 6, Bankbook (passbook), Check, Voucher

Interface

- Basic: RS232, parallel IEEE 1284
- Optional: Second Serial RS232, USB 2.0 (high speed)

Sharing mode

- Between two users

Emulation

- Olivetti: PR40, PR50, PR2, PR2E
- IBM: PPII, X24, 4722, 4748, 9068
- Others: OKI, EPSON, 1600K, HPR4915, HITACHI, SHINKO

Noise

- < 52 dBA

Document Handling

- Feed wide: 65 - 245 mm
- Single sheet Length: 70 - 797 mm
- Passbook High: 110 - 245 mm
- Passbook Width: 165 - 220 mm
- Completely flat paper feed
- Automatic border
- Automatic thickness (max thick 2.6 mm)
- Automatic Alignment

Ribbon Cartridge

- 5 million or 10 million characters

Operating Environment

- 220V / 50Hz & 110V / 60Hz
- 5.2W (standby)
- 50W (printing)

Certification & Regulatory

CE, Energy Star, CCC, RoHS



Dimension (WxDxH)

- 384 x 280 x 199 mm
- 15.12" x 11.65" x 8.03"

Weight

9.5 Kg / 10.5 Kg with magnetic reading

Operating system

- Windows® 2000;
- Windows® XP;
- Windows® Vista (32 & 64 bits);
- Windows® 7 (32 & 64 bits)



Optional

- Magnetic Strip Reader/Write
- MICR reader (CMC7, E13B)
- Scanner
- Display LCD

Scanner Characteristic

Resolution [dpi]	Duplex	Speed mm/s	Size	Rigid	Driver
200/300/600	Y	500			TWAIN



Dasa-Rägister
EN ISO 9001:2008
IQ-0311-05



Dasa-Rägister
EN ISO 14001:2004
IE-0711-01

Company with Quality System certified by Dasa and Environment-Rägister SpA in accordance with ISO 9001:2008 and ISO 14001:2004, numbers IQ-0311-05 and IE-0711-01. Copyright © 2011 Bancor. All Rights Reserved. Specifications may change without previous notice. All contents may not be reproduced without the expressed permission of Bancor s.r.l.

